

LOS ANGELES

H-4I, L-4H

IAP.AD

RWY 09: PAPI(P2L)—GA 3.5° TCH 51'.

RWY 27: REIL. PAPI(P2L)—GA 3.5° TCH 32'.

SERVICE: S4 **FUEL** 100LL, JET A **LGT** Actvt REIL Rwy 27; MIRL Rwy 09-27; twy lgts—CTAF. PAPI Rwy 09 and 27 oper 24 hrs. Rwy 09 VGSi unusbl byd 3 NM due to terrain.

NOISE: Voluntary jet curfew 0600–1500Z±. Noise sensitive are NE–SE.

Noise abatement, tkf climb on rwy heading until 1900' MSL.

AIRPORT REMARKS: Attended 1600-0400Z†. Be alert for birds year round, various size and species. Ocnl coyote on or in/vf of rwy and twy. PPR for all military acft ctc arpt manager. PPR for all acft more than 65,000 lbs at west tsnt ramp adj to ATCT; ctc amgr. Repetitive copter trng conducted on helipads south of rwy and Twy A west of tower. No copter hover taxi on Twy A from Twy A1 up to, but not inclg, Twy A4. Fire fighting acft on and in/vof arpt. Air tankers in vicinity year-round frequently fly nstd pattern entries. TPA—2395(1000) single engine, 2895(1500) multi-engine. For fire fighting activity call arpt manager. Rwy 27 calm w/d rwy.

AIRPORT MANAGER: 760-788-3366

WEATHER DATA SOURCES: ASOS (760) 239-7043

COMMUNICATIONS: CTAF 119.875 ATIS 132.025 UNICOM 122.95

® SOCAL APP CON 132.2

TOWER 119.875 (1600-0400Z±) GND CON 121.65

®SOCAL DEP CON 127.3

CLEARANCE DELIVERY PHONE: For CD when ATCT clsd ctc SoCal Apch at 800-448-3724.

AIRSPACE: CLASS D svc 1600-0400Z±; other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE F SAN.

JULIAN (VL) (L) VORTACW 114.0 JLI Chan 87 N33°08.43' W116°35.16' 235° 17.7 NM to fld. 5560/15E.

VOR unusable:

007°–010° byd 40 NM

336°–339° byd 40 NM

344°–355° byd 40 NM

356°-006° byd 40 NM blo 14,500'

356°–006° byd 70 NM

COMM/NAV/WEATHER REMARKS: When twr clsd acft must self-announce on CTAF prior to ldg or tkof.

HELIPAD H1: H340X66 (ASPH-CONC)

HELIPAD REMARKS: Helipad parking N of rwy not open to public. Helicopter skid lds on rwy and twy prohibited. Helipad ops to helipad south of rwy restricted to 6,000 lbs or less. Helipad S of rwy unlgtd. Helipad S of rwy daytime VFR use only.

